

Access|LDAP

The screenshot shows the XigmaNAS web interface for configuring LDAP. The page title is "Access > LDAP". At the top, there is a navigation menu with items: System, Network, Disks, Access, Services, Virtualization, Status, Diagnostics, Tools, Help. The main content area is titled "Lightweight Directory Access Protocol (Client)" and includes an "Enable" checkbox. Below this, there are several configuration fields:

- URI:** A text input field with a description: "The space-separated list of URIs for the LDAP server."
- Base DN:** A text input field with a description: "The default base distinguished name (DN) to use for searches, e.g. dc=test,dc=org"
- Anonymous Bind:** A checkbox labeled "Enable anonymous bind." which is checked.
- Bind DN:** A text input field with a description: "The distinguished name to bind to the directory server, e.g. cn=admin,dc=test,dc=org"
- Bind Password:** Two text input fields for password and confirmation, with a description: "The cleartext credentials with which to bind."
- Root Bind DN:** A text input field with a description: "The distinguished name with which to bind to the directory server, e.g. cn=admin,dc=test,dc=org"
- Root Bind Password:** Two text input fields for password and confirmation, with a description: "The credentials with which to bind."
- Password Encryption:** A dropdown menu set to "clear" with a description: "The password encryption protocol to use."
- User Suffix:** A text input field with a description: "This parameter specifies the suffix that is used for users when these are added to the LDAP directory, e.g. ou=Users"
- Group Suffix:** A text input field with a description: "This parameter specifies the suffix that is used for groups when these are added to the LDAP directory, e.g. ou=Groups"
- Password Suffix:** A text input field with a description: "This parameter specifies the suffix that is used for passwords when these are added to the LDAP directory, e.g. ou=Users"
- Machine Suffix:** A text input field with a description: "This parameter specifies the suffix that is used for machines when these are added to the LDAP directory, e.g. ou=Computers"
- Additional Parameters:** A text area containing: "ldap_version 3", "timelimit 30", "bind_timelimit 30", "bind_policy soft", "pam_ldap_attribute uid". Below the text area is a description: "These parameters are added to ldap.conf."

At the bottom left of the configuration area is a "Save" button. At the bottom of the page, there is a copyright notice: "Copyright © 2018 XigmaNAS® <info@xigmanas.com>".

From: <https://www.xigmanas.com/wiki/> - XigmaNAS

Permanent link: https://www.xigmanas.com/wiki/doku.php?id=documentation:setup_and_user_guide:access_ldap

Last update: 2018/07/08 16:57

