

# Rsync Client

The default configuration for Rsync client on XigmaNAS is to copy from a source directory on a remote machine to a destination directory on the local XigmaNAS machine.

System Network Disks Services Extensions Access Status Diagnostics Advanced Help

**Rsync job**  Enable

**Local share (destination)**  ...  
Path to be shared.

**Remote Rsync Server**   
IP or FQDN address of remote Rsync server.

**Remote module (source)**

**Who**

**Synchronization time**

Minutes					Hours		Days			Months	Week days
<input type="radio"/> All					<input type="radio"/> All		<input type="radio"/> All			<input type="radio"/> All	<input type="radio"/> All
<input checked="" type="radio"/> Selected ..					<input checked="" type="radio"/> Selected ..		<input checked="" type="radio"/> Selected ..			<input checked="" type="radio"/> Selected ..	<input checked="" type="radio"/> Selected ..
0	12	24	36	48	0	12	1	13	25	January	Sunday
1	13	25	37	49	1	13	2	14	26	February	Monday
2	14	26	38	50	2	14	3	15	27	March	Tuesday
3	15	27	39	51	3	15	4	16	28	April	Wednesday
4	16	28	40	52	4	16	5	17	29	May	Thursday
5	17	29	41	53	5	17	6	18	30	June	Friday
6	18	30	42	54	6	18	7	19	31	July	Saturday
7	19	31	43	55	7	19	8	20	August		
8	20	32	44	56	8	20	9	21	September		
9	21	33	45	57	9	21	10	22	October		
10	22	34	46	58	10	22	11	23	November		
11	23	35	47	59	11	23	12	24	December		

Note: Ctrl-click (or command-click on the Mac) to select and de-select minutes, hours, days and months.

**Description**

**Advanced Options**

**Recursive**  Recurse into directories.

**Remote rsync daemon**  Run without requiring remote rsync daemon. (Disabled by default)

**Times**  Preserve modification times.

**Compress**  Compress file data during the transfer.

**Archive**  Archive mode.

**Delete**  Delete files on the receiving side that don't exist on sender.

**Quiet**  Suppress non-error messages.

**Preserve permissions**  This option causes the receiving rsync to set the destination permissions to be the same as the source permissions.

**Preserve extended attributes**  This option causes rsync to update the remote extended attributes to be the same as the local ones.

**Reverse direction**  This option causes rsync to copy the local data to the remote server.

**Extra options**   
Extra options to rsync (usually empty). Please check the [documentation](#).

Services|RSYNC

From: <https://www.xigmanas.com/wiki/> - XigmaNAS

Permanent link: [https://www.xigmanas.com/wiki/doku.php?id=documentation:setup\\_and\\_user\\_guide:services\\_rsync\\_client](https://www.xigmanas.com/wiki/doku.php?id=documentation:setup_and_user_guide:services_rsync_client)

Last update: 2018/10/02 15:19

